

8812

- 1 -

CLAIMS:

1-31. (Canceled)

- 5 32. (Currently Amended) A method of synchronizing a plurality of local clocks of a plurality of USB devices ~~to be synchronized~~, each of said plurality of local clocks corresponding to ~~each a respective~~ one of a said plurality of USB devices, the plurality of USB devices being
- 10 connected to a common USB host via a USB tree so that said plurality of local clocks of said plurality of USB devices are in phase and at a common frequency, comprising:
- transmitting by the common USB host to each of said plurality of USB devices one or more first
- 15 specific signal structures;
- monitoring local USB signals at each of said plurality of USB devices for said one or more first specific signal structures;
- generating a plurality of local reference
- 20 signals, each local reference signal corresponding to each respective one of said plurality of USB devices, each local reference signal being generated by each respective one of said plurality of USB devices from at least one of said one or more first specific signal structures received
- 25 at each of said plurality of USB devices;
- locking a plurality of frequencies of said plurality of local clocks at said plurality of USB devices, each frequency corresponding to a respective one of said plurality of local clocks, and each frequency
- 30 being locked to each corresponding one of said plurality of local reference signals to a predetermined degree;
- designating a USB device in said USB tree as a master USB device for monitoring USB data traffic to and from each of said plurality of USB devices;
- 35 transmitting by the common USB host one or more second specific signal structures to each of said plurality of USB devices and transmitting specified

9/12

- 2 -

response signals corresponding to said one or more second specific signal structures from each of said plurality of USB devices;

5 monitoring for said one or more second specific signal structures and for said specified response signals with said master USB device;

generating first event triggering signals local to said master USB device corresponding to decoding of at least one of said one or more second specific signal structures;

10 generating second event triggering signals local to said master USB device corresponding to decoding of said specified response signals from said plurality of USB devices;

15 measuring respective time intervals between said first and second event triggering signals for said plurality of USB devices, each time interval corresponding to each one of said plurality of USB devices;

determining a plurality of relative propagation times with respect to a reference USB device selected from said plurality of USB devices, each relative propagation time corresponding to each one of said plurality of USB devices other than a reference USB device selected from said plurality of USB devices, each relative propagation time being determined with respect to said reference USB device by determining a difference between the time interval of said reference USB device and the time interval of each corresponding one of said plurality of USB devices other than said reference USB device;

20 determining whether a temporal adjustment or phase offset is required for each local clock of said plurality of local clocks to result in said plurality of local clocks being in phase;

35 for each local clock requiring a respective temporal adjustment or phase offset, transmitting said respective temporal adjustment or phase offset to each corresponding USB device of said plurality of USB devices;

10812

- 3 -

and

adjusting the phase of each local clock requiring
a temporal adjustment or phase offset on the corresponding
USB device according to said respective temporal

5 adjustment or phase offset.

33. (Currently Amended) A method as claimed in claim 32,
wherein at least some of said plurality of local clocks
are shifted in phase by a desired amount.

10

34. (Currently Amended) A method for synchronously
triggering and thereby initiating or stopping one or more
processes, comprising:

15 synchronizing asaid plurality of local clocks of
said plurality of USB devices according to the method of
claim 32;

monitoring traffic local to each of said
plurality of USB devices for a trigger request signal and
for a trigger command signal, indicative respectively of
20 ~~an~~ initiating trigger request and of a trigger command;

transmitting said trigger request signal with
said USB host to each of said plurality of USB devices to
prepare said plurality of USB devices to each execute said
initiating trigger request;

25 configuring said plurality of USB devices to
respond to said trigger request signal by configuring
themselves to perform said one or more processes upon
receipt of said trigger command signal;

transmitting said trigger command signal with
30 said USB host to each of said plurality of USB devices;
and

decoding said trigger command from said trigger
command signal with each of said plurality of USB devices
and thereby configuring said plurality of USB devices to
35 initiate or stop said one or more processes at a common
time;

whereby said one or more processes can be

11/8/12

- 4 -

initiated or stopped upon receipt by said plurality of USB devices of said trigger command signal from said USB host.

35. (Previously Amended) A method as claimed in claim 34,
5 wherein said trigger request signal comprises a USB packet signal structure, any command sequences sent to the plurality of USB devices, or any data sequences sent to the plurality of USB devices.

10 36. (Original) A method as claimed in claim 34, including transmitting said trigger request signal and said trigger command signal in a predetermined sequence.

37. (Currently Amended) A method as claimed in claim 34,
15 wherein said trigger command signal comprises a USB packet signal structure, any command sequences sent to the plurality of USB devices, or any data sequences sent to the plurality of USB devices.

20 38. (Currently Amended) A method as claimed in claim 34, wherein each of said plurality of USB devices includes a local USB decoding device, said local USB decoding device comprising a microcontroller, a microprocessor, a field programmable gate array or any other element capable of
25 decoding data structures within each of said plurality of USB devices.

39. (Previously Amended) A method according to claim 34,
30 wherein said trigger request signal comprises OUT tokens, IN tokens, ACK tokens, NAK tokens, STALL tokens, PRE tokens, SOF tokens, SETUP tokens, DATA0 tokens, DATA1 tokens, or other predetermined bit patterns.

40. (Canceled)
35

41. (Previously Presented) A method according to claim 34, wherein said trigger command is encoded into said USB data

12 of 12

- 5 -

traffic.

42-50. (Canceled)

5 51. (Previously Presented) A method as claimed in claim
34, including configuring said plurality of USB devices to
in concert initiate or stop said one or more processes.

10 52. (Previously Presented) A method as claimed in claim
34, wherein said one or more processes are a plurality of
processes and the method includes configuring each of said
plurality of USB devices to initiate or stop one or more
of said plurality of processes.

15 53. (Previously Presented) A method as claimed in claim
34, wherein said one or more processes are a plurality of
identical processes.

20 54. (Previously Presented) A method as claimed in claim
34, wherein said one or more processes are a plurality of
processes that includes at least two processes that are
different.